McLAREN 675LT



	3 rd Service (3 years or 45,000 k	m (30,000 m	iles))			
Please check vehicle odometer reading and d	ate of registration against Mileage and Periodic Dependan	t Operations p	rior to carryin	ng out service	Coupe service time: 2.65 ur Spider service time: 2.75 ur	
Customer:					· ·	
Vehicle registration:	VIN:	Date:				
Colour:	km/miles:	Invoice/job	number:			
Address:	,	Customer c	ontact detail	ils:		
					(Telephon	e number)
					·	
					(Ema	il address)
VEHICLE ACCEPTANCE (CUSTOMER F	PRESENT FROM 1.1 TO 1.4)					
1.0 Vehicle pre-checks		Completed	Not Completed		Comments	
1.1 Check for wheel locking key (if supplied) and towi	ing eye					
1.2 Check tyres for damage, crack formations and co	rrect orientation					
1.3 Check condition of wheel rims and wheel bolts (mark graphic below where applicable)						
1.4 Check condition of paint and bodywork (mark graphic below where applicable)						
what graphic below where applicables		1				
				P		
		F)-(B		A A		
				<i>(</i>)		
				//		
				1 94		
		20000000				
		annin				
		100				73/
				>		
				3		
	(D=dent, S=scratch, X=dam	age, C=chip)				
Comments:						
1.5 Check McLaren Retailer Portal for any outstandin	g campaigns applicable to the vehicle					-



VEHICLE EXTERIOR AND FLUID CHECKS (ENSURE BODY PROTECTION IS FITTED)

2.0	Two technicians will be required for step 2.1	Completed	Not Completed	Comments
2.1	Check operation of exterior lighting and parking sensors (if fitted)			
2.2	Check/adjust fluid level of windscreen washer system			
2.3	Check condition of wiper blade (replace if required)			
2.4	Check condition of window glazing and exterior light glazing			
2.5	Check condition of door, luggage compartment lid and engine cover seals			
2.6	Check operation of fuel filler flap manual opening mechanism			
2.7	Check operation of controls and adjusters in general (hinges, doors, luggage compartment lid, engine cover, tonneau and Retractable Hard Top (RHT))			
2.8	Check/adjust fluid level of brake system			
2.9	Check/adjust fluid level of power steering system			

INTE	NTERIOR FUNCTION CHECKS						
3.0	Carry out instrument cluster checks	Completed	Not Completed	Comments			
3.1	Check battery charge status						
3.2	Check operation of Airbrake using Active Dynamics Panel						
3.3	Check engine oil level - Refer to associated procedures						
3.4	Check operation of Tyre Pressure Monitoring System (TPMS)						
3.5	Check operation of indicator, hazard and warning lamps						
4.0	Carry out interior function checks	Completed	Not Completed	Comments			
4.1	Check operation of central locking and alarm system						
4.2	Check operation of interior controls (switches, lights, windows)						
4.3	Check operation of door mirrors (including powerfold function), rear view mirror and sun visors						
4.4	Check condition and operation of seats, seat belts and seat belt buckles (ensure seat belts are not twisted)						
4.5	Check brake pedal free play						
4.6	Check operation of Electronic Parking Brake (EPB)						
4.7	Check operation of vehicle lift function (if fitted)						

MECHANICAL CHECKS

5.0	O Secure and lift vehicle on lifting platform - Refer to associated procedures							
5.1	Check and record tyre pressures (bar/psi)	Front left:	Front right:	Rear left:	Rear right:	Completed	Not Completed	Comments
3.1	(adjust if required)							
5.2	Measure and record tyre tread depth (mm)	Front left:	Front right:	Rear left:	Rear right:	Completed	Not Completed	Comments
	Outside							
	Centre							
	Inside							
5.3	5.3 Check front and rear ball joints for play							
5.4	5.4 Check front and rear track rods for play							





MECHANICAL CHECKS - CONTINUED

6.0	Remove wheels - Refer to associated procedures	Completed	Not Completed	Comments
6.1	Check brake pads (replace if required)			
6.2	Visually check condition of brake discs - Refer to associated procedures (Weigh Carbon Ceramic Matrix (CCM) brake discs when brake pads are replaced)			
6.3	Check Electronic Parking Brake (EPB) pads (replace if required)			
6.4	Check/clean brake disc cooling ducts			
7.0	Remove rear wheel arch liners - Refer to associated procedures			
8.0	Remove all under floors - Refer to associated procedures	Completed	Not Completed	Comments
8.1	Check all visible suspension system components for correct routing, leaks and damage			
8.2	Visually check suspension bolts for secure seating			
8.3	Check Z-bar drop links and bushes for play			
8.4	Check all visible cooling system components for correct routing, leaks and damage			
8.5	Check condition of all radiators (clean as required)			
8.6	Check all visible steering components for leaks and damage			
8.7	Check engine and transmission for leaks and damage			
8.8	Check condition of air filter - Refer to associated procedures (replace if required)			
8.9	Replace engine oil and filter (only in accordance with McLaren Service Plan, dealer recommendation or at customer request) - Refer to associated procedures (If carried out allow an additional time of 0.50)			
9.0	Install all under floors - Refer to associated procedures			
10.0	Install rear wheel arch liners - Refer to associated procedures	Completed	Not Completed	Comments
10.1	Install wheels - Refer to associated procedures (ensure correct tyre orientation)			
10.2	Torque wheel bolts (130 Nm)			
10.3	Check exhaust emission label (market specific)			
10.4	Check/adjust fluid level of cooling system			

MECHANICAL CHECKS - SPIDER ONLY

11.0	Retractable hard top	Completed	Not Completed	Comments
11.1	Set Retractable Hard Top (RHT) to maintenance position, clean and grease rollers between shell panels with Kluber Polylub GLY 801 $$			
11.2	Apply Carbaflo XTR5-50F lubricant on Retractable Hard Top (RHT) seals - Refer to Service Information Bulletin 11 A 041			

DYNAMIC TEST

12.0 Road test	Completed	Not Completed	Comments
12.1 Carry out road test - maximum 15 minutes/10 km (6 miles)			
12.2 Check operation of navigation system (if fitted)			



Date of publication: 01st April 2016



FINAL OPERATIONS

13.0	Carry out final vehicle diagnostic check using McLaren Diagnostic System (MDS)	Completed	Not Completed	Comments
13.1	Check vehicle software level (update if required)			
13.2	Read out fault memory and clear errors			
13.3	Carry out service indicator reset			
14.0	Carry out final vehicle check and documentation sign off	Completed	Not Completed	Comments
14.1	Check operation of all keys, locks and key fobs			
14.2	Check expiry dates of fire extinguisher/tyre inflation kit (if fitted)			
14.3	Report and rectify all recorded defects			
14.4	Complete, sign and stamp Service and Warranty Guide			

Technician Name: Dealer Stamp: Technician Signature:	Comments:	
	Technician Name:	Dealer Stamp:
Technician Signature:	Tooming in rights.	Pouror ocump.
Technician Signature:		
Toomison organization.	Technician Signature:	
	recommendan organization.	





ASSOCIATED PROCEDURES

ASSOCIATED PROCEDUR	Document Number	Document Title
3.3	AA-RM-04F02-01-007	Check oil level
5.0	AC-RM-02A04-04-007	Lift vehicle on lifting platform
6.0, 10.1	AC-RM-03B03-01-001	Remove/Install wheel
6.2	AC-RM-03C01-01-006	Cleaning/Checking carbon ceramic brake disc (CCM)
7.0, 10.0	AC-RM-02A02-03-001	Remove/Install wheel arch liner - Rear
8.0, 9.0	AA-RM-02A04-04-001	Remove/Install floor panel - Engine / fuel tank
8.0, 9.0	AC-RM-02A04-04-002	Remove/Install floor panel - Front
8.0, 9.0	AC-RM-02A04-04-003	Remove/Install floor panel - Tunnel
8.0, 9.0	AC-RM-02A04-04-004	Remove/Install floor panel - rear diffuser
8.0, 9.0	AA-RM-02A04-04-005	Remove/Install floor panel - Rear lower extension
8.0, 9.0	AC-RM-02A04-04-008	Remove/Install floor panel - Transmission
8.0, 9.0	AC-RM-02A04-04-006	Remove/Install skid blocks / tyre spoilers / front guide vanes / rear guide vanes
8.8	AC-RM-04F01-02-002	Remove/Install air filter
8.9	AC-RM-04F02-01-011	Drain/Fill fluid - Engine oil
11.2	11 A 041	Retractable Hard Top seal lubricant application procedure

